

www.landforce.in



MECHANIZED AGRICULTURE FOR PRODUCTIVITY

Rigid Cultivator - Standard Duty



Rigid Cultivator - Standard Duty

- ❖ Heavy Box Frame
- ❖ High tensile plated fasteners
- ❖ Cat-II hitch geometry
- ❖ Less maintenance required
- ❖ Reversible shovel
- ❖ Good Quality Shovels



Landforce Rigid Cultivator “Standard Duty” is designed to withstand toughest work conditions to hard soils. The Tiller has heavy-duty shanks for positive penetration. It breaks up hard top soil, uproots stubbles and leaves the ground perfectly worked.

TECHNICAL SPECIFICATION

Model	CVS9RA	CVS11RA	CVS13RA
Frame	Square Pipe 72 x 72 x 6		
Tine Type	22 mm profile cut		
No of Tines	9	11	13
Spare Angle	50 x 8 mm		
Linkage	Front, Rear		
Length	2010 mm	2460 mm	2914 mm
Width	675 mm		
Height	1160 mm		
Hitch Category	Cat – II		
Weight (kg) Approx	195	228	265

**Company reserves the rights to change/amend products specifications without any prior notice.*

www.landforce.in
info@landforce.in
[+917837494949](tel:+917837494949)

DASMESH MECHANICAL WORKS
 AMARGARH, DISTT- SANGRUR, PUNJAB - 148022, INDIA

