



MECHANIZED AGRICULTURE FOR PRODUCTIVITY

Rotary Tiller Standard Duty

SUPREMO



Rotary Tiller Standard Duty

SUPREMO

- ❖ Robust Design and moderate structure
- ❖ Compatible with all Tractors
- ❖ Powder coated and then assembled
- ❖ Less Maintenance Cost
- ❖ Smooth working
- ❖ Traceability upto material is maintained.



Supremo is built to withstand the rigors of commercial jobs. The tiller is designed to go all day after day in the most demanding jobs. Seed bed is prepared with one or two passes and is suitable in removing and mixing residue of maize, wheat, sugarcane etc. which helps to improve soil health. Suitable for hard soil and tends to achieve greater depth penetration resulting in moving and pulverizing more soil.

TECHNICAL SPECIFICATION

Characteristics	4 Feet	5 Feet	6 Feet	7 Feet	8 Feet
Overall Length (Mm)	1520	1800	1950	2200	2440
Overall Width (Mm)	1020				
Overall Height (Mm)	1050				
Working Width (Mm)	1220	1500	1670	1930	2160
Tractor Hp	25	30	35	40	45
Hitch Category	Cat II				
No Of Blades L/C Type (80 X 7)	30	36	42	48	54
No Of Blades L/C Type (40 X 7)	42	48	54	54	66
No Of Blades J Type	60	66	72	78	84
Gear Box Type	Multi	Single / Multi	Single/ Multi	Multi	Multi
Side Transmission Type	Gear Drive				
Max Working Depth	150 Mm				
Rotor Diameter With Blades	430				
Pto Safety Device	Shear Bolt Type				
Pto	540/1000				
Weight (Kg.)	355/360/375	380/385/400	405/410/425	425/430/445	450/455/470

*Company reserves the rights to change/amend products specifications without any prior notice.

www.landforce.in
 info@landforce.in
 +917837494949

DASMESH MECHANICAL WORKS
AMARGARH, DISTT- SANGRUR, PUNJAB - 148022, INDIA

