

www.landforce.in



MECHANIZED AGRICULTURE FOR PRODUCTIVITY

Rotary Tiller Light Duty

VIVO



Rotary Tiller Light Duty

VIVO

- ❖ Light in Weight
- ❖ Robust Design
- ❖ Low maintenance cost
- ❖ Each part is powder coated
- ❖ Traceability is to material is maintained



Vivo is Specially designed for soft and loose soil. Its light weight technology makes it perfect for puddling in paddy fields. The helical-shaped rotor on the Rotary Tillers decreases horsepower required to drive units. They are designed so they enter the field at different times for more efficiency. These are sized right for subcompact tractors and are designed to till soil for seedbed preparation.

TECHNICAL SPECIFICATION

Characteristics	4 Feet	5 Feet	6 Feet	7 Feet	8 Feet	5 Feet	6 Feet
Side Drive	Gear Drive						
Gear Box	Multi Speed					Single Speed	
Min. Tractor HP Required	25	30	35	40	45		
Total Width (inch/cm)	60	71	77	87	96	30	35
Working Width (inch/cm)	48	59	66	76	85	71	77
Working Depth (inch/cm)	4 inch to 6 inch					59	66
Working Depth Control	Skids fitted as standard equipment						
PTO Speed (rpm)	540/1000						
Rotor Speed (rpm)	180-220						
Weight (kg) Approx. Without Side Disc	355/360/375	380/385/400	405/410/425	425/430/445	450/455/470	370	390
Number of Blades	30/42/60	36/48/66	42/54/72	48/60/78	54/66/84	36	42

**Company reserves the rights to change/amend products specifications without any prior notice.*

 www.landforce.in
 info@landforce.in
 +917837494949

DASMESH MECHANICAL WORKS
AMARGARH, DISTT- SANGRUR, PUNJAB - 148022, INDIA

