



MECHANIZED AGRICULTURE FOR PRODUCTIVITY

Sub Soiler 1 Tine - Std Duty



Sub Soiler 1 Tine - Std Duty

- ❖ Landforce Sub Soiler is a farming equipment used to till very dry and condensed soil. Crops planted in soil that is dry and condensed often fail due to inadequate nutrients and water.
- ❖ Landforce Sub Soiler properly till soil that's helps to produce maximum crop growth.



Landforce Sub Soiler is a tractor mounted implement used to loosen and break up soil at depths below the level of a traditional disk harrow or rototiller.

TECHNICAL SPECIFICATION

Model	Standard Duty		Heavy Duty	
	SSS-1	SSS-3	SSH-3	SSH-5
Number of Tines	1	3	3	5
Number of Shank Position	1	5	5	9
Working Depth	610		610	
Working Width	70 mm	950 mm	950 mm	1850 mm
Tyne Size	152 x 36 mm		152 x 36 mm	
Frame Size	254 x 90 x 926 mm	254 x 90 x 1069 mm	427 x 100 x 1073 mm	487 x 100 x 1920 mm
Weight (Kg.) Approx	126 Kg	260 Kg	310 Kg	490 Kg
Tractor Power	45-55	80-95	80-95	100-125

**Company reserves the rights to change/amend products specifications without any prior notice.*

🌐 www.landforce.in 📧 info@landforce.in ☎️ +917837494949

DASMESH MECHANICAL WORKS
AMARGARH, DISTT- SANGRUR, PUNJAB - 148022, INDIA

landforce™