

/IECHANIZED AGRICULTURE FOR PRODUCTIVIT

## Spring Cultivator - Standard Duty



## Spring Cultivator - Standard Duty



Landforce "Standard Duty" Spring Cultivator is designed to withstand toughest work conditions to hard soils. The Tiller has heavy-duty shanks for positive penetration. It breaks up hard top soil, uproots stubbles and leaves the ground perfectly worked.

## **TECHNICAL SPECIFICATION**

| Model              | CVS9S                  | CVS11S              | CVS13S               |
|--------------------|------------------------|---------------------|----------------------|
| Frame              | Channel 75 x 40 x 5    | Channel 75 x 40 x 5 | Channel 100 x 50 x 5 |
| Tines              | 15 x 19 Forged         |                     |                      |
| Spring             | Od-50, wire dia - 10mm |                     |                      |
| Pair Flat          | 50 x 8 mm              |                     |                      |
| Length             | 2030 mm                | 2488 mm             | 2946 mm              |
| Width              | 805 mm                 |                     |                      |
| Height             | 1150 mm                |                     |                      |
| Hitch Category     | Cat – II               |                     |                      |
| Weight (kg) Approx | 210                    | 238                 | 320                  |
| Min HP             | 35                     | 45                  | 55                   |

<sup>\*</sup>Company reserves the rights to change/amend products specifications without any prior notice.

www.landforce.in info@landforce.in +917837494949

DASMESH MECHANICAL WORKS AMARGARH, DISTT- SANGRUR, PUNJAB - 148022, INDIA

